

LAND CORNER RECORD

Index: C10	Corner: Center West Sixteenth corner of Section 4	State of Indiana - Hoosier National Forest		
Section: 4	Township: 7N	Range: 1E	P.M.: 2nd	County: Monroe
Coordinate:	Lat./N: 1392551.26	Lon./E: 3141199.63	Datum: NAD83(sft)	

CORNER HISTORY: (Chronological history of corner)


1.) Date of Survey:	Surveyor:	Monument:	Recording Information:		Monument Photograph: 
7/17/1861	I.S. Buskirk	Unknown	L.S. Book 2, Page 59		
Reference Objects:	Species:	Diameter:	Bearing:	Distance:	
	White Oak	20 inch	N 40 E	20 links	
	White Oak	15 inch	N 11 E	15 links	
Evidence Found:					
Monument Found:	1/2 inch Rebar				
2.) Date of Survey:	Surveyor:	Monument:	Recording Information:		
4/23/1993	Stephen Smith	None	Provided by USFS		
Reference Objects:	Species:	Diameter:	Bearing:	Distance:	
Evidence Found:					
Monument Found:	1/2 inch Rebar				

ACCESSORIES: Describe new BTs & witness objects established to perpetuate existing evidence.

Reference Objects:	Species:	Diameter:	Bearing:	Distance:
	White Oak with Mag Nail	11 inch	S 9° W	34.65 ft
	White Oak with Mag Nail	24.5 inch	N 2° W	71.6 ft
	Pignut Hickory with Mag Nail	16 inch	S 53° E	49.74 ft
Monument Found or Set:	3 inch aluminum monument with a cap stamped "C-W1/16 S4 T7N R1E 2011"			

MONUMENT SKETCH


NARRATIVE REFERENCE: (Describe location relative to nearby features: roads, fences, terrain features, etc..)



The location of this monument is approximately 85 feet West of a North-South running gravel drive and approximately 65 feet SouthWest of a clearing.

SECTION DIAGRAM

PERPETUATION RECORD: (Describe work done to perpetuate or preserve the existing monument or position)



Corner Location = ●

Center West Sixteenth corner of Section 4; A 1/2-inch rebar was found 0.2 feet above grade. This corner was referenced by Buskirk in 1861 and a stone was most likely set at that time, although the survey does not mention a monument at the corner. In 1969 this corner was noted as a "sandstone with chiseled + " by Jerry Tracey, L.S. The position of this stone was calculated per the prior McCord property deed by Stephen Smith, L.S. as shown on a 1993 survey of part of the East Half of the Southwest Quarter of Section 4. The location of the found 1/2 rebar matches the record distances shown on the Smith survey within 1.14 feet. The 1/2-inch rebar was accepted as marking the 1/16th corner and was replaced with a 3 inch aluminum monument with a cap stamped "C-W1/16 S4 T7N R1E 2011". The said 1/2 inch rebar was buried below grade beside the aluminum monument.

Section: 4

Prepared By: BRG

Date: 12/2011

Referenced on BRG survey recorded as InstNo.2012002880

Accepted by the Monroe County Surveyor Review Board on August 6, 2019.